



Agilent Digital Multimeters



Agilent Technologies













Designed to handle your toughest assignments in various applications

Agilent's digital multimeters lead the industry in speed and accuracy and have a proven track record for reliability. Our digital multimeters offer exceptional performance and ease of use provided by intuitive front panels and standards-based programming interfaces.

From a bench top to a test rack to a handheld, there's an Agilent digital multimeter that's right for the job.



Index

Model No.	Description	Digits of resolution	Measurement speed (reading/s)	Basic measurements	Connectivity & Software	More details on page:
 U3401A/U3402A	Benchtop DMM, dual display Elegantly simple and affordable DMMs with basic and good capabilities	4½ (U3401A) 5½ (U3402A)	N/A	DC, true RMS AC, AC+DC voltage & current, 2-wire resistance (and 4-wire resistance for U3402A), frequency, diode, continuity	N/A	4, 5
 U3606A	DMM and DC power supply in one box Halves bench/rackspace need for two instruments	5½	37	DC and true RMS AC voltage and current, 2- and 4-wire resistance, capacitance, frequency, diode test, continuity. 30-W dual-range output 30 V/1 A and 8 V/3 A with OVP/OCV, auto scan/ramp and square wave generator	USB 2.0, GPIB	6, 7
 34401A	Benchtop DMM Industry standard for accuracy, speed, measurement ease and versatility	6½	1000	DCV, ACV, DCI, ACI, 2- and 4-wire resistance, frequency & period, continuity, diode test	GPIB, RS-232, Intuilink software-provides a toolbar in Microsoft Word and Excel to import multimeter data for further analysis	8, 9
 34405A	Benchtop DMM, dual display Low-cost DMM with accuracy, speed and versatility	5½	19	DCV, ACV, DCI, ACI, 2-wire resistance, frequency & period, continuity, diode test, capacitance, temperature	USB 2.0, Intuilink software-provides a toolbar in Microsoft Word and Excel to import multimeter data for further analysis	10, 11
 34410A/34411A	Benchtop DMM, dual display Highest through-put of benchtop DMMs, best choice for system use	6½	10,000 (for 34410A) 50,000 (for 34411A)	DCV, ACV, DCI, ACI, 2- and 4-wire resistance, frequency & period, continuity, diode test, capacitance, temperature	LAN, USB 2.0, GPIB plus LXI class C compliant, Intuilink software-provides a toolbar in Microsoft Word and Excel to import multimeter data for further analysis	12, 13
 34420A	Nano volt/mΩ meter Very accurate, low-level measurements	7½	250	DCV, DCI, 2- and 4-wire resistance, 2 channel scanning, temperature	GPIB, RS-232, Intuilink software	14, 15
 3458A	Benchtop DMM The fastest, most flexible and most accurate multimeter by Agilent Ideal multimeter for demanding applications	8½	100000 (@ 4½ digits)	DCV, ACV, DCI, ACI, 2- and 4-wire resistance, frequency & period, temperature	GPIB	16, 17
 U1210 Series	Handheld clamp meter For convenient high current measurements	3½	7	DCV, ACV, DCI, ACI, 2-wire resistance, capacitance, temperature, frequency, diode test, continuity	N/A	19, 20
 U1240 Series	Handheld DMM Feature-rich and robust DMMs	4	7	DCV, DCI, ACV, ACI, 2-wire resistance, frequency, capacitance, continuity, switch counter, harmonic ratio, temperature, diode test, 4-20 mA % scale	N/A	21, 22
 U1250 Series	Handheld DMM Versatile, high performance DMMs	4½	7	DCV, DCI, ACV, ACI, 2-wire resistance, frequency, capacitance, continuity, diode test, dB, temperature, frequency counter, 4-20 mA % scale	IR-USB	23, 24
 U1401A/U1401B	Handheld multi-function calibrator/meter Calibrator and DMM in one tool	4½	3	DCV, ACV, DCI, ACI, 2-wire resistance, temperature, frequency, diode test, continuity, pulse width, duty cycle	IR-USB	25, 26
 U2741A	USB Modular DMM Compact, with plug-and-play simplicity	5½	100	DCV, ACV, DCI, ACI, 2- and 4-wire resistance, frequency & period, continuity, diode test, temperature	USB 2.0	27, 28
Accessories compatibility chart						29, 30

Basic + Good = Elegant Simplicity

U3400 Series 4 ½ and 5 ½ digit multimeters




Key features


- Up to 120 000 counts resolution
- Up to 0.012% basic DCV accuracy
- 11 basic measurements – DC, AC, AC+DC (True RMS), voltage and current
- Up to six built-in math functions – dBm, Relative, Min/Max, Compare, Hold
- Dual display on bright VFD
- Selectable resolutions for variable measurement speeds
- Kensington lock slot security



www.agilent.com/find/low-cost-dmm



Models and specifications



Ordering Information

U3401A 4 ½-digit Dual Display Digital Multimeter
 U3402A 5 ½-digit Dual Display Digital Multimeter

Each U3400 series includes:

- Quick Start Guide
- Product Reference CD
- Certificate of Calibration (CoC)
- 34138A Test Lead Kit
- AC Power Cord

Options:

U3400A-100 USB to RS232 Cable
 U3400A-1CM Rack Mount Kit
 U3400A-1CN Dual Flange Kit

Accessories:

34138A Test Lead Kit
 U1161A Extended Test Lead Kit
 34330A Current Shunt (30 A)
 34133A Precision Electronic DMM Test Leads
 11059A Kelvin Probe Set
 U3400A-1CM Rack Mount Kit



Technical Datasheet:
 Literature no. 5990-3970EN

DCV Accuracy	0.02%
Reading speed	N/A
Measurement functions	DCV, ACV, DCI, ACI, 2-wire and 4-wire resistance, true RMS ACI, frequency, diode, continuity
Type of connectivity	N/A

The real two instruments in one box



U3606A multimeter | DC power supply



Key features

2-in-1-box convenience

Full-featured DMM


- 9 measurement functions, including capacitance
- 8 built-in math functions
- 4-wire milliohm measurement with 0.001 mW resolution

Full-featured DC Power Supply


- 30 W, dual-range 30 V/1 A and 8 V/3 A
- Ability to source constant-voltage and -current directly
- OVP and OCP load protection
- Auto ramp and scan for multi-level DC bias testing



www.agilent.com/find/hybrid-multimeter



Models and specifications



Ordering Information

U3606A 5 ½ -digit Digital Multimeter | DC Power Supply

Each U3606A comes with:

- Quick Start Guide
- Product Reference CD
- Agilent IO Library Suite
- Certificate of Calibration
- U8201A Combo Test Lead Kit
- USB 2.0 High-Speed Type-A to Type B Cable
- AC Power Cord

Warranty options

R-51B-001-3C Extended warranty from one year to three years

R-51B-001-5C Extended warranty from one year to five years

Accessories

- U3606A-1CM Rack Mount Kit
- U8201A Combo Test Lead Kit
- U8202A Electronic Test Lead Kit (for DMM function)
- 34133A Precision Electronic Test Leads (for DMM function)
- 34330A Current Shunt (30 A) (for DMM function)
- 34136A 40 kV High-voltage Probe (for DMM function)
- 11059A Kelvin Probe Set
- 11062A Kelvin Clip Set (for DMM function)
- E3600A-100 Test Lead Kit (for DC power supply function)



Technical Datasheet:
Literature no. 5990-3971EN

DCV Accuracy	0.025 %
Speed	37 readings/second
Measurement functions	DCV, ACV, DCI, ACI, 2-wire and 4-wire resistance, true RMS ACV/ACI, frequency, capacitance, diode, continuity
Type of connectivity	GPIB, USB 2.0

Uncompromising Performance for Benchtop and System Testing



34401A 6 1/2 digit multimeter



Key features

- 12 measurement functions
- 1000 V maximum input
- 15 ppm or 0.0015% basic DCV accuracy (24-hour)
- 0.06% basic ACV accuracy (1 year)
- 1000 readings per second direct to GPIB
- GPIB and RS-232 standard
- SCPI commands standard
- Intuilink Connectivity Software included



www.agilent.com/find/34401A



Affordable yet feature-rich measurement tool

34405A 5 ½ digit multimeter




Key features


- Up to 120 000 counts resolution
- 16 built-in measurement functions including temperature and capacitance
- 0.025% 1-year DC voltage accuracy
- USB 2.0
- SCPI compatible
- Agilent IO Library Suite and DMM Intuilink connectivity software included



www.agilent.com/find/34405A



Models and specifications



Ordering Information

34405A 5 1/2-digit Digital Multimeter

Each 34405A series includes:

- Test Lead Kit
- Test Report
- AC Power Cord
- USB Interface Cable
- Quick Start Guide
- User's and Service Guide
- Product Reference CD-ROM
- Agilent IO Library Suite CD-ROM

Options:

Opt. 1CM Rack Mount Adapter Kit

Accessories:

- 34132A Precision Electronics DMM Test Leads
- 34330A 30 A Current Shunt
- E2308A 5 kΩ Thermistor Temperature Probe



Technical Datasheet:
Literature no. 5989-4906EN

DCV Accuracy	0.025%
Reading Speed-DCV	19 readings/second
Measurement	DCV, ACV, DCI, ACI, 2-wire resistance, true RMS ACV/ACI, frequency, capacitance, temperature, diode, continuity
Type of connectivity	USB 2.0

Affordable yet feature-rich measurement tool

34410A/34411A 6 ½ digit multimeter



Agilent 34410A 6 ½-digit high-performance DMM

Key features

- 10,000 readings/s @ 5 ½-digits direct to PC
- 1,000 readings/s @ 6 ½-digits direct to PC
- DCV, ACV, DCI, ACI, 2-wire and 4-wire resistance, frequency, period, continuity and diode test
- Capacitance and temperature measurements
- Expanded measurement ranges
- Data logger with 50k reading non-volatile memory



www.agilent.com/find/34410A

Agilent 34411A 6 ½-digit enhanced-performance DMM

Key features

All features of the 34410A plus:



- 50,000 readings/s @ 4 ½-digits direct to PC
- 1 million volatile reading memory
- Analog level triggering
- Programmable pre/post triggering



www.agilent.com/find/34411A



12



Models and specifications



Ordering Information

34410A 6 1/2-digit Digital Multimeter

34411A 6 1/2-digit Digital Multimeter

Each 34410A/34411A includes:

- Test Lead Kit with Probes and SMT Attachments
- Test Report
- AC Power Cord
- USB Interface Cable

Options:

Opt.1CM Rack Mount Kit

Opt. ABA Printed Manual Set (English)

Opt. 0B0 Delete Printed Manual Set (full documentation included on CD ROM)

Opt. A6J ANSI Z540 Compliant Calibration

Accessories:

11059A Kelvin Probe Set

11060A Surface Mount Device (SMD) Test Probes

11062A Kelvin Clip Set

34131A Hard Transit Case

34162A Accessory Pouch

34171B Input Terminal Connector

34172B Input Calibration Short

34330A 30 A Current Shunt

E2308A 5 kΩ Thermistor Temperature Probe

34190A Rack Mount Kit with Filler Panel



Technical Datasheet:

Literature no. 5989-3738EN

DCV Accuracy	0.003 %
Reading Speed-DCV	10,000 readings/second
Measurement	DCV, ACV, DCI, ACI, 2-wire and 4-wire resistance, true RMS ACV/ACI, frequency, capacitance, diode, continuity
Type of connectivity	GPIB, USB 2.0, LAN (LXI Class C)

Nano-volt performance at a micro-volt price

34420A 7 ½ digit multimeter



Key features



- 7 ½ digits resolution
- 100 pV/ 100 n1/2 sensitivity
- 1.3 nVrms/8 nVpp noise performance
- Built-in low noise 2 channel scanner
- Direct SPRT, RTD, Thermistor, and thermocouple measurements




www.agilent.com/find/34420A



14



Models and specifications



7 ½-digit resolution

Built-in low noise two channel scanner with ratio and difference functions

Three resistance modes are included:

- Standard
- Low-power
- Voltage-limited for dry-circuit testing

Selectable analog or digital filtering

Ordering Information

34420A NanoVolt/Micro-Ohm Meter

Each 34420A includes:

- Low-thermal Input Cable (34102A)
- Low-thermal Shorting Plug (34103A)
- Kelvin Clip Set (11062A)
- Operating Manual
- Service Manual
- Quick Reference Guide
- Test Report with Cal

Options:

- 34420A-1CM Rack Mount Kit (P/N 5062-3972)
- 34420A-ABA English Localization
- 34420A-ABD German Localization: Translated Operating Manual
- 34420A-ABF French Localization: Translated Operating Manual
- 34420A-ABJ Japanese Localization: Translated Operating Manual
- 34420A-A6J ANSI Z540 Compliant Calibration

Accessories:

- 34102A Low-thermal Input Cable with Copper Spade Lugs
- 34103A Low-thermal Shorting Plug
- 34104A Low-thermal Input Connector
- 34131A Transit Case
- 34161A Accessory Pouch



Technical Datasheet:
Literature no. 5968-0161EN

DCV Accuracy	0.003 %
Reading Speed-DCV	250 readings/s
Measurement	DCV, 2-wire and 4-wire resistance, temperature
Type of connectivity	GPIB, RS-232

Shattering performance barriers of speed and accuracy



3458A 8 1/2 digit multimeter





Key features


- 8 1/2 to 4 1/2 digits resolution
- Up to 100,000 readings/sec (4.5 digit)
- Maximum sensitivity: 10 nV
- Programmable integration times from 500 ns to 1 sec
- Two-source (10 V, 10 k Ω) calibration, including ac
- Self-adjusting, self-verifying auto-calibration for all functions and ranges, including ac
- Multimeter Language (ML) compatible



www.agilent.com/find/3458A



Models and specifications



Ordering Information

3458A Multimeter

Each 3458A includes:

- Test Lead Set (34118B)
- Power Cord
- Operating Manual
- Calibration Manual
- Assembly Level Repair Manual
- Quick Reference Guide

Options:

- 3458A-001 Extended Reading Memory (expands total to 148 kbytes)
- 3458A-002 High Stability (4 ppm/year) Reference
- 3458A-A6J ANSI Z540 Compliant Calibration
- 3458A-907 Front Handles Kit
- 3458A-908 Rack Mount Kit
- 3458A-909 Rack Mount Kit with Handles
- 3458A-ABD German Manual
- 3458A-ABF French Manual
- 3458A-ABJ Japanese Manual
- 3458A-ABZ Italian Manual

Accessories

- 11053A Low Thermal Test Lead Pair, Spade Lug to Spade Lug, 0.9 m
- 11174A Low Thermal Test Lead Pair, Spade Lug to Banana, 0.9 m
- 11058A Low Thermal Test Lead Pair, Banana to Banana, 0.9 m
- 11059A Kelvin Probe Set (4-wires, 1 m)
- 11062A Kelvin Clip Set
- E2308A 5 kΩ Thermistor Temperature Probe
- 10833A/B/C/D GPIB Cable



Technical Datasheet:
Literature no. 5965-4971E

DCV Accuracy	0.0008 %
Reading Speed-DCV	Up to 100,000 readings/second (4.5 digits)
Measurement	DCV, ACV, DCI, ACI, 2-wire and 4-wire resistance, frequency
Type of connectivity	GPIB

Handheld and modular DMMs

Go further with Agilent handheld digital multimeters



Recognizing the increasing demand for tools that are portable, accurate and yet affordable, Agilent offers handheld digital multimeters, multi-function calibrator/meter and clamp meters for installation and maintenance activities. Other handheld instruments include digital oscilloscopes, capacitance and LCR meters.

These award-winning handheld tools meet critical safety standards while providing a wealth of features and world-class accuracy. Each handheld comes in vivid orange cases that provide greater visibility and serves to highlight investment protection through feature sets that go beyond those of typical handhelds.



USB Modular digital multimeter - a bench that fits into a bag

Agilent's USB modular DMM is the innovative solution for laboratory environments. It provides bench instrument capabilities in an affordable, space-saving form factor. It can be used as a standalone instrument or mounted in a chassis with other modules. This enables flexible configurations and quick setup in electronic functional test and troubleshooting applications.

Other USB-based modular instruments include oscilloscopes, function generator, source measure unit, switch matrix and data acquisition products such as multi-function measurement modules, digital input/output devices and thermocouple input.

Handle big currents – safely

U1210 Series handheld clamp meters



Key features

- Large clamp opening of 52 mm or 2"
- High measurement capability of up to 1000 A for AC, DC or AC+DC
- CAT III 1000 V/CAT IV 600 V safety rating
- Includes full-featured DMM with resistance, capacitance, frequency and temperature functions
- High resolution measurements – measure current as low as 0.01 mA
- Peak hold capability



www.agilent.com/find/clampmeter



Models and specifications



Ordering Information

- U1211A Clamp Meter
- U1212A Clamp Meter
- U1213A Clamp Meter

Each clamp meter is shipped with:

- Test Leads with 19-mm and 4-mm Tips
- Soft Carrying Case
- Standard Alkaline 9 V Battery
- Quick Start Guide
- Certificate of Calibration

Accessories:

- U1168A Standard Test Lead Kit
- U1162A Alligator Clips
- U1175A Soft Carrying Case
- U1186A K-type Thermocouple and Adapter



Technical Datasheet:
Literature no. 5990-5083EN

DCV Accuracy	0.50%
Reading speed	7 readings/s
Measurement	DCV, ACV, DCI, ACI, 2-wire resistance, capacitance, temperature, frequency, diode test, continuity
Type of connectivity	N/A

Check more, fix more, spend less

U1240 Series handheld multimeters





Key features

- 10 000 display counts resolution
- 0.09% basic DCV accuracy
- True RMS AC measurement
- Basic functions – ACV, DCV, ACI, DCI, resistance, frequency, diode, continuity tests
- Advanced functions – capacitance, temperature, MINMAX recording
- Adjustable backlighting – 2 intensity levels
- Manual data logging (U1242A/U1242B only)
- Built-in switch counter, harmonic ratio (U1242A/U1242B only), dual/differential temperature capabilities (U1242A/U1242B only)
- CAT III 1000 V and CAT IV 600 V safety protection



www.agilent.com/find/handheldmm



Models and specifications



Ordering Information

U1241A/U1241B Digital Multimeter
U1242A/U1242B Digital Multimeter

Each handheld comes with:

- Four 1.5 V AAA Alkaline Batteries
- Certificate of Calibration
- Test Probe Leads (19-mm and 4-mm tips)
- Quick Start Guide

Accessories:

U1162A Alligator Clips	U1181A Immersion Probe type K
U1163A SMT Grabbers	U1182A Industrial Surface Probe
U1164A Fine Tip Test Probes	U1183A Air Temperature Probe
U1168A Standard Test Lead Set with 4-mm Test Probes	U1184A Temperature Probe Adapter
U1169A Standard Test Leads with 4-mm Test Probes	U1185A J-type Thermocouple and Adapter
U1171A Magnetic Hanging Kit	U1186A K-type Thermocouple and Adapter
U1172A Transit Case	
U1174A Soft Carrying Case	



Technical Datasheet:
Literature no. 5989-7040EN

DCV Accuracy	0.09 %
Reading speed	7 readings/s
Measurement functions	DCV, ACV, DCI, ACI, 2-wire resistance, frequency, capacitance, temperature, diode, continuity tests
Type of connectivity	N/A

Be well equipped from the start

U1250 Series handheld multimeters





Key features

- High contrast ratio of 2000:1 and wide viewing angle of 160°*
- 50,000 counts high resolution and up to 0.025% low error rate
- Built-in square-wave generator and frequency counter
- Includes all essential accessories for electronics troubleshooting
- Smoothing function to stabilize erratic readings*
- Data logging to instrument and PC

*with U1253A/U1253B




www.agilent.com/find/handheldmm



Models and specifications



[1] U1253A/U1253B only
[2] U1252A/U1252B/U1253A/U1253B only



Best Value Portable Test Equipment, 2006



A testament to innovation and credibility, 2006



General-purpose instruments category, 2009



Category Winner, EC&M Product of the Year competition, 2009

Ordering Information

U1251A/U1251B Digital Multimeter
U1252A/U1252B Digital Multimeter
U1253A/U1253B Digital Multimeter

Each U1251A/U1252A comes with:

- Standard Test Leads (with 19-mm and 4-mm tips)
- Alligator Clips
- Battery Charger (for U1252A)
- Certificate of Calibration
- Test Report
- Quick Start Guide
- Fine Tip Test Probes
- SMT Grabber
- Carrying Case
- Mini Grabber

Each U1251B/U1252B comes with:

- Standard Test Leads (with 19-mm and 4-mm tips)
- Alligator Clips
- Battery Charger (for U1252B)
- Certificate of Calibration
- Test Report
- Quick Start Guide

Each U1253A/U1253B comes with:

- Standard Test Leads (with 19-mm and 4-mm tips)
- Alligator Clips
- Battery Charger
- Certificate of Calibration
- Test Report
- Quick Start Guide

U1253A Option

- Option 001 Bundled SMT Grabbers, Fine-tip Test Probes and Soft Carrying Case



Technical Datasheet:
Literature no. 5989-5509EN

DCV Accuracy	0.025 %
Speed	100 readings/second
Measurement functions	DCV, ACV, DCI, ACI, 2-wire and 4-wire resistance, frequency, capacitance, temperature, diode, continuity tests
Type of connectivity	IR-USB

Calibrate while you measure with just one tool

U1401A/U1401B handheld multi-function calibrator/meter



Key features

- Dual display with bright LCD backlight
- Simultaneous source and measure
- Bipolar voltage and current, square-wave, auto scan and ramp outputs
- Full-span DMM capability, including temperature and frequency measurements
- Hold and Min/Max/Average recordings
- Data logging to PC with optional



www.agilent.com/find/handheld-calibrator-meter



Models and specifications



Ordering Information

U1401A Multi-function Calibrator/Meter
 U1401B Multi-function Calibrator/Meter

Each U1401A/U1401B is shipped with:

- Calibrator/Meter Standard Test Lead Kit
- Yellow Test Lead for mA Simulation
- Protective Holster
- Rechargeable Battery Pack
- AC Power Adapter and Cord (according to country)
- Quick Start Guide
- Certificate of Calibration
- Soft Carrying Case is included for U1401A

Accessories:

- U1168A Standard Test Lead Kit
- U1162A Alligator Clips
- U1181A Immersion Temperature Probe
- U1182A Industrial Surface Temperature Probe
- U1183A Air Temperature Probe
- U1184A Temperature Probe Adapter
- U1186A K-type Thermocouple and Adapter
- U5402A Yellow Test Lead for mA Simulation
- U5481A IR-to-USB Cable
- U5491A Soft Carrying Case



Technical Datasheet:
 Literature no. 5990-3459EN

DCV Accuracy	0.003 %
Reading Speed	3 readings/s
Measurement	DCV, ACV, DCI, ACI, 2-wire resistance, temperature, frequency, diode test, continuity, pulse width, duty cycle
Type of connectivity	IR-USB

A bench that fits into your bag



U2741A 5 1/2-digit USB modular multimeter




Key features


- Up to 100 readings per second
- Up to 300 VDC with 5 1/2-digit resolution
- Frequency and temperature measurement capability
- Wide measurement ranges: 100 mVDC to 300 VDC, 10 mA to 2 A
- Compatibility with Hi-speed USB 2.0, USBTMC-USB488 standard
- Standalone and modular capabilities
- Bundled software - Agilent Measurement Manager (AMM)



www.agilent.com/find/U2741A



Models and specifications



View voltage along with time using dual display mode

Ordering Information

U2741A Digital Multimeter

Each U2741A comes with:

- 12 V, 2A AC/DC Power Adapter
- Power Cord
- Standard Test Lead
- USB Standard-A to Mini-B Interface Cable
- L-Mount Kit (used with modular product chassis)
- Agilent USB Modular Products Quick Start Guide
- Agilent Measurement Manager Quick Reference Card
- Certificate of Calibration
- Agilent USB Modular Products Reference CD-ROM
- Agilent Automation-Ready CD-ROM (contains the Agilent IO Libraries Suite)

Accessories:

- U2921A-101 USB Secure Cable, 2m
- 34138A Test Lead Set
- E2308A 5 k Ω Thermistor Temperature Probe



Technical Datasheet:
Literature no. 5989-9923EN


DCV Accuracy	0.02 %
Reading Speed-DCV	100 readings/second
Measurement	DCV, ACV, DCI, ACI, 2-wire and 4-wire resistance, frequency, temperature, diode, continuity tests
Type of connectivity	USB 2.0

Accessories Compatibility Chart

Description	U3401A	U3402A	U3606A	34405A	34401A	34410A	34411A	34420A	3458A	U1210 Series	U1240 Series	U1250 Series	U1401A/ U1401B	U2741A
11059A Kelvin Probe set		✓	✓		✓	✓	✓		✓					
11060A Surface Mount Device probe					✓	✓	✓							
11062A Kelvin Clip set		✓	✓		✓	✓	✓	✓	✓					
34102A Low thermal input cable								✓						
34103A Low thermal shorting plug								✓						
34104A Low thermal Input Connector								✓						
34133A Precision Electronic test leads	✓	✓	✓	✓	✓	✓	✓							
34134A DC coupled current probe					✓	✓	✓							
34136A High Voltage probe			✓	✓	✓	✓	✓							
34138A Test Lead set	✓	✓		✓	✓	✓	✓							✓
34330A 30 A Current Shunt	✓	✓	✓	✓	✓	✓	✓		✓					
U8201A Combo Test Lead kit			✓											
U8202A Electronic Test Lead kit			✓	✓										
E2308A Thermistor Temperature Probe				✓	✓	✓	✓		✓					✓
E3600A-100 Test Lead Kit			✓											
34131A Transit case					✓	✓	✓	✓						
34161A Accessory Pouch					✓			✓						
34162A Accessory Pouch						✓	✓							
34171B Input Terminal block					✓	✓	✓							
34172B Calibration Short					✓	✓	✓							
34190A Rackmount Kit			✓		✓	✓	✓	✓						
34191A 2U Dual Flange Kit			✓		✓			✓						
34194A Dual Lock Link Kit					✓	✓	✓	✓						
34308A Thermistor Kit						✓	✓		✓					
34398A RS-232 Cable, 9-pin (F) to 9-pin (F)					✓									
Y1133A Low-thermal External DMM Scanning Kit					✓	✓	✓							
U1161A Extended Test Lead kit	✓	✓								✓	✓	✓	✓	
U1580A DMM Terminal Test Lead Set										✓	✓	✓	✓	
34137A Deluxe Test Lead set									✓					
U1168A Standard Test Lead Kit (with 19-mm tips and 4-mm tips)										✓	✓	✓	✓	

Description	U3401A	U3402A	U3606A	34405A	34401A	34410A	34411A	34420A	3458A	U1210 Series	U1240 Series	U1250 Series	U1401A/ U1401B	U2741A
U1169A Test Probe Leads (with 19-mm tips and 4-mm tips)											✓	✓		
U1180A Thermocouple adapter and Lead Kit										✓	✓	✓		
U1162A Alligator clips										✓	✓	✓	✓	
U1163A SMT grabbers										✓	✓	✓	✓	
U1164A Fine-tip test probes										✓	✓	✓	✓	
U1583A AC Current Clamp											✓	✓		
U5402A Yellow Test Lead for mA simulation													✓	
U1181A Immersion Temperature Probe										✓	✓	✓	✓	
U1182A Industrial Surface Temperature Probe										✓	✓	✓	✓	
U1183A Air Temperature Probe										✓	✓	✓	✓	
U1184A Temperature Probe Adapter										✓	✓	✓	✓	
U1185A J-type thermocouple and adapter											✓	✓		
U1186A K-type thermocouple and adapter										✓	✓	✓	✓	
U1171A Magnetic Hanging Kit											✓	✓		
U1172A Transit Case (Aluminium-clad)											✓	✓		
U1174A Soft Carrying Case											✓	✓		
U1175A Soft Carrying Case										✓				
U1591A Carrying Case (PVC Leather)													✓	
U1170A Battery Charger adapter												✓		
U1173A IR-to-USB cable												✓		
U5481A IR-to-USB cable													✓	

Linking up your instruments to the PC



Agilent GPIB and Instrument Control Products helps connect your instruments to PC easily, reliably and affordably. From legendary GPIB cables to the world's first LXI Class B triggering device, see how each provides seamless integration of your instrument no matter where they are placed in your system. www.agilent.com/find/io

www.agilent.com

www.agilent.com/find/dmm

For more information on Agilent Technologies' products, applications or services, please contact your local Agilent office. The complete list is available at:

www.agilent.com/find/contactus

Product specifications and descriptions in this document subject to change without notice.

Americas

Canada	(877) 894 4414
Latin America	305 269 7500
United States	(800) 829 4444

Asia Pacific

Australia	1 800 629 485
China	800 810 0189
Hong Kong	800 938 693
India	1 800 112 929
Japan	0120 (421) 345
Korea	080 769 0800
Malaysia	1 800 888 848
Singapore	1 800 375 8100
Taiwan	0800 047 866
Thailand	1 800 226 008

Europe & Middle East

Austria	43 (0) 1 360 277 1571
Belgium	32 (0) 2 404 93 40
Denmark	45 70 13 15 15
Finland	358 (0) 10 855 2100
France	0825 010 700*
	*0.125€/minute
Germany	49 (0) 7031 464 6333
Ireland	1890 924 204
Israel	972-3-9288-504/544
Italy	39 02 92 60 8484
Netherlands	31 (0) 20 547 2111
Spain	34 (91) 631 3300
Sweden	0200-88 22 55
Switzerland	0800 80 53 53
United Kingdom	44 (0) 118 9276201

Other European Countries:

www.agilent.com/find/contactus

Revised: October 1, 2009

Remove all doubt

Our repair and calibration services will get your equipment back to you, performing like new, when promised. You will get full value out of your Agilent equipment through-out its lifetime. Your equipment will be serviced by Agilent-trained technicians using the latest factory calibration procedures, automated repair diagnostics and genuine parts. You will always have the utmost confidence in your measurements. For information regarding self maintenance of this product, please contact your Agilent office.

Agilent offers a wide range of additional expert test and measurement services for your equipment, including initial start-up assistance onsite education and training, as well as design, system integration, and project management.

For more information on repair and calibration services, go to:

www.agilent.com/find/removealldoubt

© Agilent Technologies, Inc. 2010
Printed in USA, March 24, 2010
5990-5315EN



Agilent Technologies